



www.calgro.com.mx

Tel. (33)3609-1649

ventas@calgro.com.mx


## FASTENERS



## HEAVY DUTY T-BOLT 4140 STEEL

### Heavy-Duty Hoist Rings

- Use Heavy-Duty Hoist Rings for added lifting safety to avoid eyebolt twisting, bending and breaking when lifting heavy, angular, unbalanced loads
- Hoist rings pivot and swivel to compensate for pitch, roll and sway when lifting unbalanced loads - pivots 180°, swivels 360°
- Minimum safety factor is 5:1
- Meets Military Specification MIL-STD 1365 (11) or MIL-STD 209



Thread Size	Working Load Limit (Lbs.)			Dimensions (Inches)							Recommended Torque Load (Ft./Lb.)	Part No.	Pkg. Qty.
	Straight Pull	45° Lift	90° Lift	A Radius	B	C	D	E	F	G			
3/8-16	1,000	1,000	1,000	0.65	2.29	0.96	0.44	1.06	3.23	1.25	12	58655	1
1/2-13	2,500	2,500	2,500	1.00	3.50	1.50	0.75	1.00	5.31	1.89	28	58656	1
5/8-11	4,000	4,000	4,000	1.00	3.50	1.50	0.75	1.00	5.31	1.89	60	58657	1
3/4-10	5,000	5,000	5,000	1.00	3.50	1.50	0.75	1.00	5.31	1.89	100	58658	1
1-8	10,000	10,000	10,000	1.40	5.10	2.05	1.00	1.45	7.00	2.81	230	58659	1